




CONTROL TRANSFORMERS

THREE PHASE

75VA 7500VA

This range of three phase transformers has been designed to deliver maximum power rating with minimum weight and size. The open type construction is based on lamination stacks, clamped between angle irons with base fixings. In order to cover individual requirements the customer has a choice of four termination types:- stud. block. copper busbar or flying leads. All transformers in this range are varnish vacuum impregnated and fitted with an earth screen between primary and secondary windings. Floor or wall mounted sheet steel cases are available across the whole range.



RATING (VA) / DIMENSIONS (mm) / WEIGHT (kg)							
OPEN TYPE							
VA	A	B	C	D	E	F dia	WGT
75	125	195	80	146	48	5	3.75
100	125	195	85	146	54	5	4.25
125	125	195	90	146	60	5	5
175	140	245	85	203	48	5	5.75
250	140	245	95	203	60	5	7.25
350	140	245	110	203	73	5	9
500	175	290	105	240	63	6	11
750	175	290	125	240	76	6	13.5
1000	175	290	130	240	89	6	16.5
1250	180	340	125	240	76	6	17.5
1500	180	340	135	240	89	6	21.5
1700	180	340	150	240	102	6	27
2000	255	360	165	330	102	10	32
3000	255	360	180	330	115	10	38
3500	255	360	195	330	127	10	45
4000	305	435	220	380	127	10	57
5000	305	435	230	380	140	10	65
6000	305	435	245	380	152	10	75
7000	305	435	255	380	165	10	85
7500	375	485	245	455	140	10	95

